



# Product Data Sheet

## DECORATIVE RANGE Granular Marble

### DESCRIPTION

Multitex Granular Marble is an acrylic aggregate pre-mix, generally applied by a steel trowel in single application to give a relatively smooth, dense finish; it is supplied in fine and coarse grades in colours obtainable naturally. Composed mainly of 100% acrylic emulsions, concentrated anti-fungicides and quality graded crushed marble, granite or river stone.

### USES

Granular Marble is a durable marble, granite or pebble based coating, ideal for providing an attractive finish on correctly prepared domestic & commercial, exterior & interior wall surfaces. Generally it is trowel applied and finished to achieve an even coarse or fine granular appearance protective coating displaying excellent resistance to weathering and excellent exterior durability, it dries to give the original look and colour of the marble.

### FEATURES & BENEFITS

- Excellent water resistance when completely dry
- Excellent vapour permeability
- Excellent flexibility
- Excellent durability
- Strong adhesion
- Low maintenance
- Easy to apply
- Water based
- Coating warranty when correctly applied as per Multitex recommended system
- Easy & safe clean up

### SUITABLE SUBSTRATES – when properly prepared and primed

- Cement Render surface
- AAC (Autoclaved Aerated Concrete) rendered surface
- Fibre Cement Sheeting (Fibro/Blue board)
- Rendered expanded polystyrene
- Rendered Clay and Concrete Brickwork
- Rendered Concrete blocks
- Tilt panel walls
- Other primed exterior surfaces

## Product Data Sheet

## DECORATIVE RANGE Granular Marble

---

### PROPERTIES, APPLICATION & TECHNICAL DATA

**Packing:** 15 Litre plastic pail/drum

**Product Type:** Coarse- grain size -2mm Marble,  
Fine- grain size -1mm (marble)

**Appearance:** Thick gritty viscous liquid

**Type:** Water Based acrylic emulsion

**Gloss Level:** Clear Semi Gloss film on grain

**Thinner** not recommended

**Volume Solids:** @35%

**Specific Gravity:** (nominal) ~1.5 - 1.75

**Coverage:** **Coarse** @ 3-4 SqM per 15L pail/bucket

**Fine** @ 6-7 SqM per 15L pail/bucket

**Number of Coats:** 1(one)

**Wet film per coat:** Recommended grain size

**Touch Dry:** 90 Minutes (25°C 50%RH)

**Toxicity:** Lead free.

**Shelf life (unopened pails):** 24 months maximum from date of manufacture.

### Application Method



**Clean Up** Clean all equipment with water after use.

### APPLICATION GUIDE

*ENSURE PRODUCT AND COLOUR ARE CORRECT BEFORE APPLICATION*

#### Surface Preparation

Note: Ensure alkaline surfaces have aged for 30 days minimum.

- Areas not to be coated should be masked and protected.
- All surfaces to be coated must be clean, sound, free from contaminants including; oil, mould release, dust, dirt, silicone, mud, grease, salt, efflorescence, animal droppings and any loose or flaking material.
- All substrates must be primed, normally with Multi Prime. Where substrates are chalky &/or prone to dusting Multi Grip must be used.
- Metal, tie wire, etc. on surface must be removed or treated against corrosion.
- Surface imperfections and irregularities should be leveled and patched and completely flush to surrounding surfaces.

#### Application Procedure and Equipment

- Mix thoroughly with a power mixer, ensure consistency before application.
- Generally applied with a steel trowel along the substrate, commence from the top, working to the bottom. Continue trowelling surface until surface is even and compact. As soon as surface loses its milky appearance firmly trowel to ensure an even finish.

#### Important Information

- Granular Marble must only be applied in air temperatures between 10°C and 30°C on a dry substrate and must be protected from rain and frost for the first 24 hours or finished work must be protected from rain, frost and severe weather conditions until fully dried
- Avoid application in hot or windy conditions or when rain is expected within 24 hours.
- Apply at recommended spreading rate to ensure optimum performance.



# Product Data Sheet

## DECORATIVE RANGE Granular Marble

### SAFETY & HANDLING

MSDS No.:

Refer to MSDS for Multitex Granular Marble before use. For further information on Material Safety Data Sheets, call the Tech – Info line on 1300 333 333 or visit [www.multitex.com.au](http://www.multitex.com.au)

When working with MultiTexture observe the usual precautions for handling acrylic water based products including:

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water.
- Full pails are HEAVY. Wear protective footwear and seek assistance if necessary.
- Storage- no specific issues, store away from food and drink.

### FIRST AID MEASURES

#### **Ingestion**

- If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.

#### **Eye**

- Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

#### **Advice to Doctor**

- Treat symptomatically.

### LIMITATIONS

- Multitex Corporation Pty Ltd provides a material only replacement warranty caused by any defect in manufacture when used in conjunction with the full Multitex Wall-Coating System for a period of ten years when applied correctly by a skilled and experienced applicator in accordance with all current application recommendations as per and the Multitex Wallcoating System composition recommendation, including but not limited to, substrate type and preparation, application rates and methods, prevailing weather conditions and protection of finished work. Application dates, product batch numbers and quantities must be recorded and supplied as a minimum to commence potential product failure investigation.
- Multitex cannot accept responsibility for variations in colour, strength, appearance or workability resulting from on-site mixing procedures, wrong application methods and substrate conditions. Please check the colour before use, the applicators is responsible for applying the correct colour and product.
- Multitex provides no warranty, expressed or implied, against damage due to movement of the substrate or structure.



## Product Data Sheet

## DECORATIVE RANGE Granular Marble

---

### TRANSPORT AND STORAGE

**Pack size** 15 Litre

**Weight @** 23 Kg

**Dangerous Goods Class** NA

**Shipment Name** ~ Not dangerous goods. No special transport requirements.

**Storage** ~ Store in a cool place with lid pressed in, above 4°C, do not stack more than three high.

**Flash point** NA

**UN Number** NA

**Package Group** NA

#### Disclaimer

The information provided herein is considered correct at the time of publication. It is the responsibility of those using this information to check that it is current prior to specifying or using any of the products or coating systems. Any advice, recommendation or information provided by any of the officers of Multitex Corporation Pty Ltd in relation to goods manufactured by it for their use and application, is given in good faith and is believed by Multitex Corporation Pty Ltd to be appropriate and reliable. However, this advice, recommendation and information are provided without liability or responsibility excluding or limiting responsibility under relevant Government acts.